

Tracked Impact Crushers

1412T Large Secondary Crusher



Performance Specification

Production Rate	Max Feed Size	Reduction Ratio	Engine Size	Feeder Belt
350+ TPH*	300mm (12")	Up to 20:1	CAT C13 (Tier 3/Tier4)	Yes

* Depending on material density and set-up

Dimension Specification

Transport Dimensions			Working Dimensions		
Height	Width	Length	Width	Length	Weight (Est.)
3560mm (11' 8")	3200mm (10' 6")	15,100mm (49' 7")	3850mm (12' 7")	17,030mm (55' 10")	42,700kgs (94,137 lbs)

1412T

The Tesab 1412T is a Tracked, Large Secondary Impact Crusher designed to accept a Wide Variety of Material Sizes while producing a Superior Shaped Cubical Product.

The 1412T features a heavy duty feed hopper and belt feeder design while the crusher unit incorporates a 1200mm (47") diameter rotor along with the unique Tesab crushing path design providing a high reduction ratio.

Suited for both secondary and tertiary applications the 1412T can work stand alone or integrate easily into existing crushing & screening operations.



Features & Benefits

- Up to 350+ tonnes per hour Production Rate
- Produces a Superior Cubical Shaped Product
- Suitable for both Secondary and Tertiary Applications
- Innovative Design for Fast Setup and Easy Transportation

TESAB

Engineered for Power, Built to Last